

BAUM DELIVERS

Stackers, Presser-Stackers & Banders



For compressing single signatures from one-up to multiple-up production.

Baum BAS/SA Pressing Unit w/ Shingle Delivery

- Two pairs hard chrome-plated pressing rollers, separately adjustable.
- Fast and easy thickness adjustment with eccentric handles.
- Easy position change of infeed belts.
- Infinite variable speed adjustment.
- Mobile on wheels.
- Maximum pressure 20,000 N.
- Adjustable infeed height from 15.75 to 39.38 inches (400-1000mm)
- Maximum product thickness .31" (8mm)
- Speed: 50-180 m/min infinitely adjustable.
- Power 1kw



For compressing single signatures from one-up to multiple-up production.

Baum BAS/FSA Horizontal Press Stacker


- Fast and easy format adjustment without use of tools.
- Infinitely variable speed adjustment.
- Mobile on wheels.
- Maximum stack height of 15.75" (400mm)
- Maximum pressure 20,000 N.
- Adjustable infeed height from 15.75 to 39.38 inches (400-1000mm)
- Maximum product thickness .31" (8mm)
- Speed of 50-180 m/min infinitely adjustable.
- Delivery height of 34.44" (875mm)
- Power 1kw



For compressing and stacking single signatures from one-up to multiple-up production.

Baum BAS/STB Vertical Press Stacker

- Fast and easy format adjustment without use of tools.
- Infinitely variable speed adjustment. Mobile on wheels,
- Maximum stack length of 31.5"(800mm)
- Maximum pressure of 20,000 N.
- Speed of 50-180 m/min.
- Adjustable infeed height of 17.71" to 39.38" (450-1000mm)
- Delivery height of 34.44" (875mm)
- Maximum product thickness .31" (8mm)
- Power 1 kw.



BAUM

PO Box 728, 1660 Campbell Rd, Sidney OH 45365
Phone 1-800/543-6107 or 937/492-1281
Fax 937/492-7280
Internet: <http://www.baumfolder.com>
e-mail: baumfolder@baumfolder.com

BAUM DELIVERS

Stackers, Presser-Stackers & Banders



VDS Vertical Delivery Stacker

For collecting small folded product that cannot be controlled on conventional shingling. Multiple streams can be collected. Includes remote control.



2-Tiered Stacker

Provides mobility, height adjustment, and angular adjustment for collecting folded product. Has a 37.75" belt length and 48" total collection length.



Mobile Stacker Kit

Adds mobility and height adjustment in one convenient kit that includes locking casters. Hang-on delivery stacker has 16.5" belt length and 27" maximum collection length.

Baum PAB 800 Presser/ Stacker/ Bander

For counting, compressing, stacking, and banding signatures from one-up to multiple-up production.

- Fast and easy format adjustment without use of tools
- Infinitely variable speed adjustment
- Banding using single roll
- Banding using paper or film
- Mobile on wheels
- From (1) to (6) ups can be achieved
- Product maximum thickness of single signature: 5/16 in. (8mm)
- Maximum Stack Height not compressed: 6 in. (150mm)
- Infeed Height: 23.63 in. to 38.50 in. (600-980mm) Adjustable
- Delivery Height: 32 in. (810mm)
- Speed: 131-656 Feet/Min. (40-200 M/min)
- Pressure: 20,000 N Adjustable
- Banding Rate: Max. 27 per min.
- Electrical Power: 4.3kw 230/400V/ 3ph/50/60 Hz.

