

**HVF FEEDER / LOADER
THICK SHINGLE SPECIFICATIONS**

Product Sizes: Head to foot max. 356mm (14 in.)
 Head to foot min. 127mm (5 in.)
 Spine to face max. 330mm (13 in.)
 Spine to face min. 76mm (3 in.)

Product Thickness: 2 to 72 pages

Spine Direction: Leading / edge / optional Straight Shooter Attachment.

Electrical Power Supply: Standard, 460VAC, 230VAC, 115VAC



Continuous Feeding of Products

Baumfolder offers a unique solution to increase the feeding capability as compared to the traditional bottom fed feeders using the Baumfolder HVLF Feeder. Sensors are located in the hopper that keep a selected amount of product in the hopper until the entire load of product is fed from the horizontal transfer area. Easy, continuous loading of product is performed on a long belted transfer table that insures non-stop production. Additional loading capacity can be added by adding the optional Baumfolder extension tables for an additional six to ten feet of loading capacity.

The Baumfolder HVLF feeder can feed a wide variety of products that are thick to thin and in variable select shapes. Some examples are feeding flat cardboard boxes, cardboard shapes, catalogs for insertion for ecommerce order fulfillment, and more!

This solution provides:

- Longer run times between loadings.
- Continuous, non-stop operation
- Ability to load and feed heavier, bulky, products with continuous feeding.
- Combine multiple Baumfolder HVLF feeders and program to feed into a lug conveyor or flow wrapper.
- Program to feed onto a conveyor for an auto bagging or carton closing line

Air Consumption: approx. 6 SCFM

Loading Length – 53”

Dimensions: Hopper loading height:	(44 inches)
Overall width: main conveyor	(14 inches)
Overall length:	(94 inches)
Overall height:	(52 inches)
Height adjustment:	(4.50 inches)

Side Guides: Center justification

Safety Standards: CE and ANSI B65.2 1999

1660 Campbell Rd
 Sidney, Ohio 45365
 800-543-6107
www.baumfolder.com