

PRODUCT SPECIFICATION WORKSHEET

What is the rate per/box per minute customer is trying to achieve?

PRINTED PAGES per insert (Invoice, Packing slip, Personalized sales info?)

1 page	All the time
1 page front & back	Simplex or duplex sheets available.
2 page	All the time
1 TO 6	Variable print quantities
1 TO ?	Variable print quantities- 1 to 18 sheets completed in multiple print and fold sets.
8.5x 11"	sheet size
Preprinted forms or labels?	to be run thru the print engine
color printing	
blank and White	

SYSTEM VOLTAGE

220V / 1 PHASE
440V / 3 PHASE

What is the current box size variations

min max

		Height
		width
		length

Does the document go in or on the box?
Is there a required fold, or minimum sheet size. Should reflect min box size.
What is the height of the conveyor?
Estimated footprint or floor space available

Yes No

Will any boxes or cartons be sent down the line that will not require any inserts. If so a signal from the warehouse management system will need to be sent to the Baumfolder system.

Yes No

Barcode matching.

Consist of Scanner on inserter, that will scan barcode on printed document and match to the bar-code (must be the same as the barcode on printed document) on the carton.



BAUMFOLDER
SOLUTIONS

Baumfolder Corporation
1660 Campbell Rd, Sidney OH 45365
937.492.1281 or 800.543.6107
Baumfolder@baumfolder.com

BAUMFOLDER SPECIFICATIONS

Customer is required to scan the box FOUR (4 ZONES) ahead to provide printed information to print engine. If this increases or decreases the speed of the system will be impacted. Too far up stream Baumfolder will have to add a divert section or additional staging sections to collect printed information and insert if the line would be stopped. This prevents the copier over running the existing insert system and jamming.

Electrical discrete messages needed for interface

System Power On

Signal Box in place

Barcode pass to Conveyor

Barcode Fail to Conveyor

Inserter on to Conveyor

Carton not to have insert Optional

Barcode must be on last page and placed on

Cartons must be justified to Baum equipment

Stop line after two failures (unless otherwise specified)

Signal must be sent one zone before insertion

agreed upon location on document for verification.

with barcode leading.

SYM	REVISION	BY	E
-	-	-	-

